

Don Young Co.

DYC

Windows & Doors

The perfect execution of a masterpiece
without any compromise

Divina



Diva

ALL PVC



Diva redefines standards in the industry of patio doors. Its renewed appearance is combined to unequalled performance with respect to energy efficiency, solidity and security. The Diva patio door confirms the creators' commitment to make it an uncompromisingly superior product for either new construction or renovation projects.

Standard Features

- The Diva patio door has a 4 5/8" all PVC frame with integral nailing fin.
- The Diva patio door is offered standard with multipoint lock for added security.
- The screen can also be locked from the inside.
- Sloped sill for optimal water drainage.
- The Diva patio door is suitable for new construction or remodeling.
- All sashes are fusion welded for more strength.
- Fully reversible - can be assembled to slide left or right.
- The opening sash integrates double tandem adjustable rollers for smooth and easy operation on anodized aluminum tracks.



Warranty

Every Diva patio door is delivered with a limited warranty:
20-year on PVC.
10-year against seal failure.

Diva is a creation of



Collaboration in Action!

Sturdiness

- The Diva patio door uses heavy duty aluminum extrusions for screen.
- The vertical stiles are reinforced with metal.
- The sill is made of reinforced PVC for greater resistance.
- The Diva patio door is built with multichamber heavy duty PVC profiles for maximum strength and rigidity.

Performance

- Full perimeter weatherstrip forms a positive seal between frame and panels.
- Multichamber insulating PVC profiles to provide maximum comfort.
- Strong interlocking meeting rail for air tightness.

Options

The Diva patio door comes with a complete line of options to suit individual requirements.

- Lock and key.
- Security bar.
- Many glazing options: Low E (Argon), tinted, with or without grills.

US Standards

- Meets the AAMA/NWDA 101/1.S2-97
- SGD-R50 (72 x 80)
- NFRC tested
- HUD certified
- Energy Star qualified
- TDI qualified

Canadian Standards

- Meets CSA-A440
- Air tightness: A3
- Water Resistance: B4
- Wind load resistance: C2
- Ease of operation: E3
- Forced entry: F2
- Energy rating (LowE + Argon): -1

Sizes Available

Nominal size	Type	Frame size	Recommended Rough opening
5'0" x 6'8"	OX or XO	59 1/4" x 79 1/2"	60" x 80"
6'0" x 6'8"	OX or XO	71 1/4" x 79 1/2"	72" x 80"
8'0" x 6'8"	OX or XO	95 1/4" x 79 1/2"	96" x 80"
9'0" x 6'8"	OXO*	107 3/4" x 79 1/2"	108 1/2" x 80"
12'0" x 6'8"	OXO*	143 3/4" x 79 1/2"	144 1/2" x 80"

* 9' and 12' units are constituted of a standard 6' or 8' door mullion to a sidelite.

Don Young Co.
DYC
Windows & Doors

Dallas (214) 630-0934
Houston (713) 868-1398
San Antonio (210) 225-0352
Lubbock (806) 747-2181
Oklahoma City (405) 947-2000

www.dycwindows.com



Our Customers Assemble Energy-Efficient Windows and Doors with Thermoplast Vinyl Profiles

Custom sizes available upon request.